

# UTILIPHALT®

UtiliPhalt® is a dense surface course designed with low air-voids to create a more durable pavement. It is ideally suited for footway and highways utility reinstatement

**UtiliPhalt® is an enhanced asphalt concrete (AC) designed to aid with compaction on site. It is available as a surface course in 6mm or 10mm aggregate sizes and as a binder course in 20mm aggregate. It is made with penetration grade bitumen 70/100 - 100/150 and offers a range of PSVs**

## REPAIR & REINSTATEMENT





# UTILIPHALT®

**CONWAY  
COLLECT**  
asphalt : simplified

## WHY CHOOSE UTILIPHALT®

- ✔ UtiliPhalt® offers increased durability and product life, while reducing installation time and network disruption.
- ✔ Lower air-voids designed into the mix to reduce air and water permeation, making it easier to achieve compaction that is compliant with SROH. (Specification for the Reinstatement of Openings in Highways).
- ✔ Our UtiliPhalt® range is a 'planet-friendly' solution - it can be produced in smaller quantities and at lower temperatures at our Conway Collect depots, and is 100% recyclable, while the increased durability extends the product life.

## APPLICATION BENEFITS

- Reduced installation time, thanks to improved workability and compaction properties, resulting in less time on site.
- Increased compliance with air-voids regulations helps avoid costly remedial work and reduces network disruption.
- Less waste, as it can be produced at our Conway Collect depots in small quantities.

## APPLICATIONS

- UTILITY REINSTATEMENT
- FOOTWAYS AND FOOTPATHS
- CYCLE TRACKS

## DISCOVER THE FULL RANGE

UtiliPhalt® is available as a surface course in a 6mm or 10mm aggregate size and as a binder course in 20mm aggregate.

Available in a warm mix and in a range of PSVs for enhanced skid resistance.

**UtiliPhalt® 6** - Surface Course, Hardstone, Penetration Graded Bitumen 70/100 - 100/150

**UtiliPhalt® 6** - Surface Course, Warm Mix Hardstone, Penetration Graded Bitumen 70/100 - 100/150

**UtiliPhalt® 10** - Surface Course, Hardstone to 68 PSV (Polished Stone Value), Penetration Graded Bitumen 70/100 - 100/150

**UtiliPhalt® 10** - Surface Course, Warm Mix Hardstone to 68 PSV (Polished Stone Value), Penetration Graded Bitumen 70/100 - 100/150

## GUARANTEED COMPLIANCE

All mixtures comply fully with BS EN 13108 'Bituminous Mixtures' and the accompanying guidance notes (PD6691 Appendix B) as applicable.

Product testing complies fully with the requirements of BSEN12697 'Test Methods for Hot Mix Asphalt'.

Product installation and any subsequent testing is also compliant with BS 5944987 'Asphalt for Roads and Other Paved Areas'.

 **FM CONWAY LTD**

Conway House  
Vestry Road  
Sevenoaks Kent  
TN14 5EL

 0800 276 1122

 [AandAOrders@fmconway.co.uk](mailto:AandAOrders@fmconway.co.uk)

 [www.fmconway.co.uk](http://www.fmconway.co.uk)



For detailed guidance on material selection, laying requirements and appropriate uses, contact our Aggregates and Asphalt division: [aaproducts@fmconway.co.uk](mailto:aaproducts@fmconway.co.uk)