



AGGREGATES AND ASPHALT DIVISION

# SUREFLEX

A responsive asphalt product  
for all highway surfaces



# SUREFLEX

*SureFlex* is a thin flexible asphalt layer suitable for highway or motorway surfaces.

*SureFlex* is a 10mm or 14mm gap-graded asphaltic concrete utilising a polymer modified binder. It's thin laying characteristics minimises intervention, reduces road closure periods and enables early trafficking.

## Endurance and versatility

*SureFlex* is available in a range of aggregate sizes and manufactured using FM Conway polymer-modified binder to provide maximum strength, durability and versatility. It delivers hard-wearing, skid resistant surfaces and noise reduction of between 5 and 7dB(A) compared to traditional hot rolled asphalt.

## Certified performance

As a HAPAS certified product, the manufacture of *SureFlex* is highly regulated, with laboratory and in-situ product trial and inspections of our asphalt plants carried out by the British Board of Agrément on a regular basis.

## Guaranteed compliance

All mixtures comply fully with BS EN 13108 'Bituminous Mixtures' and the accompanying guidance notes (PD6691 Appendix B) as applicable.

Product testing complies fully with the requirements of BSEN12697 'Test Methods for Hot Mix Asphalt'.

Product installation and any subsequent testing is also compliant with BS 5944987 'Asphalt for Roads and Other Paved Areas'.



For detailed guidance on material selection, laying requirements and appropriate uses, contact our Aggregates and Asphalt division.



FM CONWAY LTD  
Conway House  
Vestry Road  
Sevenoaks  
Kent  
TN14 5EL

T 0800 276 1122  
E [aandaorders@fmconway.co.uk](mailto:aandaorders@fmconway.co.uk)  
W [www.fmconway.co.uk](http://www.fmconway.co.uk)  
 @FMConwayLtd